



2	ribbe	10	st. 00.	lf. 200x10x 310.		
2.	vinkelafstivning.	9	Huss-jern	vinkel: 90x50x12x 940		
2.	vinkelafstivning.	8	" "	vinkel: 50x50x12x3000		
4.	ribbe.	7	" "	Hagl: 200x10x 420		
4.	ribbe for fjederspændeskru.	6	" "	Hagl: 75x10x 520		
4.	ribbe for fjederspændeskru.	5	" "	Hagl: 50x10x13x 800		
4.	bæret for fjederspændeskru.	4	" "	Hagl: 150x25x1840		
4.	plade for konsol	3	" "	1000x1050x13		
4.	plade for konsol.	2	" "			
2.	vandret afstivning.	1	Huss-jern	se skit nr. 62238 pos. 1		

Sik.	Betegnelse		Pos.	Materiale kvalitet	Model nr. materiale størrelse	h ²	fastg. Vægf/sik
Tegn. Koll.	Rev.	Mid.	IL	Hålsfri:			
100	MT 8-6-50	Norm.		1:5 1:25			
000		Ref.else	Indsk.	FRICHS			
258	Pos. 10.11.11.11.11		A				
1/2-58 pos. 3 vandret af hensyn til fjeder E.L. 1/2				Styliste nr.			
finvendelse							
Diesel-el. 500/550 HK motorvogn Mo				8302			
Tegningens bemærkelse				Tegningens nummer			
Længdeafstivning med konsoller for motorbogje.				18W-8.590			
Indeks:				a x c			