



Bemærk!
Huller for tappe og bolte i pos 3 bores ved montagen.

vægt pr. lokomotiv 64 kg

12	Fjederskive 3/4"	7	Fj.st.	Magasinet	
12	Drejet bolt 3/4" WG-50 N.bl.247	6	KF.40	NK.32-Ø40	
8	Top 32 ^ø -28	5	St.00	32 ^ø -300	
16	Ribbe 120-170-16	4	"	700-500-16	
4	Krog 335-252-10	3	"	750-600-10	
16	Afstivning 45-10-56	2	St.00	45-10-1120	
4	Plade 480-120-10	1	St.37	500-500-10	
Stk.	Betegnelse	Pos.	Materiale kvalitet	Model nr. eller materiale størrelse	rå færdig vægt/stk.
Tegn.	LC-2	Ræk.		Ad.	IL
Kalk.	B.C.21-12-59	Norm.		Dato	19-6-56
Dato		Rustelse		Indeks	
28/11-56	Længden af Pos. 1 ændret fra 116-120				
	Pos 3 ændret.				A
28/11-56	Bemærkning til brug				B
	Anvendelse				
Dies-el.400hk.rangerlokomotiv				Slykliste nr. 18049	
Sikring mellem lokomotiv-kasse og bogie				Tegningens nummer 307L-13.240	
				Indtaks. 1/1	