


2	rørholder	38 x 6,5 x 110	13	st. 37.	1/2 38 x 6,5 x 230		
11	fjederstave	1/2"	10	fj. st.	magasin		
8	bolt m. møtrik	1/2" x 45 sort	11	st. 37.	— " —		
3	bolt m. møtrik	1/2" x 75 sort	10	st. 37	— " —		
1	union	1 1/4" sort	9	GF 341	— " —		
3	vinkelunion	1 1/4" sort	8	GF 98	— " —		
4	union	1 1/4" sort	7	GF 340	— " —		
2	vinkel	1 1/4" sort	6	GF 92	magasin		
1	gevindrør	1 1/4" x 4 D.S. 545	5	st. 35.29	l = 13000		
2	rørholder	32 x 6,5 x 150	4	st. 37.	1/2 32 x 6,5 x 320		
4	afslørningsjern	50 x 6,5 x 53	3	— " —	1/2 50 x 6,5 x 210		
4	holder	50 x 6,5 x 350	2	— " —	1/2 50 x 6,5 x 3400		
4	holder	50 x 6,5 x 480	1	st. 37.			
Sjh.	Befælgelse			Pos.	Materiale kvalitet	Model nr. eller materiale skærpe fsc	rd færdig Vægfjst.
Tegn.	J.P.	rev	J.P. 18/4 52	Afd.	Målestok: 1:10, 1:1		
Kølk.	J.S. 9-952	Norm.		Dato			
Dato		Rettekse					
1/2-52	diverse ændringer.				Indsk.	<div style="text-align: center;"></div>	
				A			
fløvendelse				Slyktsle nr.			
Diesel-el. 750 hk. loko.				9613.			
Tegningens benævnelse				Tegningens nummer			
Arrangement af mellemkøler.				301L-22.420.			
				Indeks:	A		